

Single Tag Printer

JP-X

Type F3

For
Single
Tags

Round
or Oval
Tag

Efficient
Tag
Feeding

Printing
Width
64mm

200mm
/sec

LAN
Optional



Hi-Speed and Stable Printing
Adjustable Feeding System as Tag Thickness
Carbon Ink Ribbon Saving



Environmental Friendly

RoHS COMPLIANT

C.M.M

Model	JP-XF3
Printing Method	Thermal Transfer Dot Matrix
Printing Density	12dots/mm(300dpi)
Printing Speed	80 to 200mm/second
Printing Width	Max. 64mm
Printing Length	50 to 300mm
Number of Print Head	1
Interface	USB2.0, Optional: LAN connector
Stacker Mechanism	Auto-descending Type (Maximum Height:150mm)
Applicable Barcode	JAN(13 . 8) 、 EAN UPC/A、 UPC/E、 2of5(Industrial) NW7、 Code39、 Code93、 Code128 ITF、 GS1-128、 GS1 Databar PDF417、 QR-code DataMatrix(ECC200)、 GS1 Composite
Media Type	Single-sheet Tags
Printable Tag Width	19 to 105 mm
Printable Length	50 to 300 mm
Overall Size	W335 x D345 x H465
Weight	22kg
Power Source	AC100V/220V 50/60Hz
Power Consumption	Less than 400VA
Accessories	Operation Manual, AC cord

MADE IN JAPAN

High-Reliability of Japanese Quality